HEUCOPLAST® EZ RED 122 PPR 122



Technical Data Sheet for Plastics

Rev. Date: 06 / 2011

Rev. No.: 0

PRODUCT DESCRIPTION	
Color Index	Pigment Red 122
C.I. No.	73915
Chemical Type	Quinacridone

FULL TONE	REDUCTION

PRODUCT PROFILE

Heucoplast EZ Red 122 P is a high strength pigment concentrate in a polyolefin carrier with excellent dispersibility.

The free flowing, non-dusting powder form of this product is suitable for automated feeding equipment.

Heucoplast EZ Red 122 P has excellent heat and light fastness and is suitable mainly for polyolefins.

PHYSICAL DATA			
Appearance	Red Powder	Red Powder	
Density [g/cm³]	0.59-0.62	DIN EN ISO 787-10	
Bulk Volume [ltr/kg]	1.90-1.95	DIN 53194	

APPLICATION PROFILE	
PE	recommended
PP	Potential use
PP Fibre	-
PVC-u	-
PVC-p	-
Rubber	-

FASTN	ESS PROPERTIES		
Migrati	on	5	DIN EN ISO 14469-4
Light F	astness	8	DIN EN ISO 105-B01
Heat R	esistance [°C]	280	DIN EN ISO 12877-2

STANDARD PACKAGING
-25kg PE Bags
- Different types of packaging are available on request

^{® =} Registered trademark of Heubach Colour Pvt. Ltd. Our product specifications and application information are based on our current knowledge. They are non-binding and cannot be taken as a guarantee. The processing company must establish the suitability of individual products itself. As their use lies beyond our knowledge and control, we cannot accept any liability relating to the use of our products in particular applications. In addition to that, the legal rights of third parties must always be considered. The specification agreed between the customer and ourselves is the basis upon which our general sales and delivery conditions are set and is the deciding factor concerning any liabilities. Our standard specification is then valid if no specification has been agreed upon between the customer and us.